

## Distributor for the Netherlands



## **HAYNES LUBRI-FILM**



Heavy Duty Lubricating Grease Packaged in tubes (1oz & 4oz), 11.25oz sprays, 12oz cartridges, pails, and drums.





NSF rated H1

**Haynes Lubri-Film** is a heavy duty sanitary lubricant with high load bearing, low friction properties. This lubricant is authorized by the NSF (rated H1) for use in food processing plants for incidental food contact. All ingredients are FDA approved.

Haynes Lubri-Film provides a protective coating to all metal parts. A thin film will retain effectiveness on bearings, slides, and other lubricated surfaces despite moisture. By staying on the work area, corrosion of metal is minimized. This sanitary lubricant is highly resistant to separation or bleed. It will not dry or gum on your equipment.

## **COMMON APPLICATIONS:**

- o POSITIVE PUMPS
- o HOMOGENIZER PISTONS
- o SIZE REDUCTION EQUIPMENT
- o PLUG VALVES
- DISPENSING UNITS
- o CENTRALIZED LUBRICATION EQUIPMENT
- o BEVERAGE EQUIPMENT
- o FREEZERS
- o STAINLESS STEEL THREADS
- o SEPARATORS
- o CLARIFIER

## TECHNICAL DATA INFORMATION

TEST	ASTM Method	Typical Test Results
Melt Point	D566	200°F
Consistency	D217	333
Viscosity(Saybolt @ 210°F)	D445	55
Viscosity(CST @ 100°C)	D2161	8
Four Ball Wear Scar Diameter, mm	D2266	0.63
Operating Range, Min °F, Max °F		-15° - 210°F
NLGI		1