

Art.-Nr. 1084940

DN	A	B	C	D	E	Reduceer laspuntstuk - DIN 11851 Welding reducing liner - DIN 11851
20 - 15	17	20	8	16	36,5	
25 - 15	22	26	10	16	44,0	
25 - 20	22	26	10	20	44,0	
32 - 20	23	32	10	20	50,0	
32 - 25	20	32	10	26	50,0	
40 - 25	20	38	10	26	56,0	
40 - 32	23	38	10	32	56,0	
50 - 25	28	50	11	26	68,5	
50 - 32	23	50	11	32	68,5	
50 - 40	26	50	11	38	68,5	
65 - 32	32	66	12	32	86,5	
65 - 40	26	66	12	38	86,0	
65 - 50	27	66	12	50	86,0	
80 - 40	36	81	12	38	100,0	
80 - 50	30	81	12	50	100,0	
80 - 65	31	81	12	66	100,0	
100 - 50	40	100	15	50	121,0	
100 - 65	40	100	15	66	121,0	
100 - 80	42	100	15	81	121,0	

Alle maten in mm - All sizes in mm

Leverbaar in 304/304L (1.4301/1.4307) & 316L (1.4404) - Available in 304/304L (1.4301/1.4307) & 316L (1.4404)

Andere kwaliteiten en afmetingen op aanvraag - Other grades and sizes on request