


## Rohrbogen in Edelstahl Elbows in stainless steel



Bauart 5 90°

DN	Ø aussen / outside			Gewicht / Stück weight / piece  kg ≈	geschweisst / welded			nahtlos seamless  1.4435/ 1.4404
	d mm	s mm	a mm		316 Ti 1.4571	304 L 1.4307	316 L 1.4404 1.4432	
10	17,2	1,6	43	0,040				●
15	18,0	1,5	49	0,050				●
	20,0	1,5	50	0,055				●
	21,3	1,6	42,5	0,060		●	●	
	21,3	2,0	42,5	0,065	●	●	●	
	21,3	2,6	42,5	0,070			●	●
20	23,0	1,5	55	0,065		●	●	
	25,0	1,5	55	0,080				●
	26,9	1,6	57,5	0,090		●	●	
	26,9	2,0	57,5	0,110	●	●	●	
	26,9	2,6	57,5	0,145				●
25	28,0	1,5	65	0,100		●	●	
	30,0	2,0	69	0,125		●	●	
	33,7	2,0	72,5	0,180	●	●	●	
	33,7	3,2	72,5	0,280				●
32	35,0	2,0	75	0,190				●
	38,0	2,0	85	0,240				●
	40,0	2,0	95	0,270		●	●	
	42,4	2,0	92,5	0,280	●	●	●	●
	42,4	2,6	92,5	0,365	●			
	42,4	3,2	92,5	0,450				●
40	44,5	2,0	100	0,310		●	●	
	48,3	2,0	107,5	0,390	●	●	●	
	48,3	3,2	107,5	0,630				●
50	54,0	2,0	122	0,460		●	●	
	60,3	2,0	135	0,610	●	●	●	
	60,3	2,6	135	0,775			●	
	60,3	3,6	135	1,080				●



## Rohrbogen in Edelstahl Elbows in stainless steel



Bauart 5 90°

DN	Ø aussen / outside			Gewicht / Stück weight / piece kg ≈	geschweisst / welded		
	d mm	s mm	a mm		316 Ti 1.4571	304 L 1.4307	316 L 1.4404 1.4432
65	70,0 x 2,0		160	0,770		●	●
	76,1 x 2,0		175	0,985	●	●	●
	76,1 x 2,3		175	1,165			●
	76,1 x 2,6		175	1,200			●
80	84,0 x 2,0		200	0,770		●	●
	88,9 x 2,0		205	1,335	●	●	●
	88,9 x 2,3		205	1,460			●
	88,9 x 2,6		205	1,750			●
100	104,0 x 2,0		250	1,900		●	●
	114,3 x 2,0		270	2,355	●	●	●
	114,3 x 2,6		270	2,900	●		●
125	129,0 x 2,0		312,5	2,790	●	●	●
	139,7 x 2,6		330	4,430	●	●	●
150	154,0 x 2,0		375	4,500	●	●	●
	168,3 x 2,6		390	6,325	●	●	●
200	204,0 x 2,0		500	7,900		●	●
	219,1 x 3,0		510	12,820		●	●
250	273,0 x 3,0		650	20.500		●	●
300	323,9 x 3,0		775	29.000		●	●