

<b>Technical file</b>		<b>ROD33-330</b>
<b>Reference</b>		
<b>Dimensions</b>	DN door	<b>296 mm</b>
	Frame height	<b>80 mm</b>
	Frame thickness	<b>2 mm</b>
	Outside dim.	<b>175 mm</b>
	Outside dim. Total	<b>417 mm</b>
	CODAP in BAR at 150°	
	Advised using pressure	<b>0,1</b>
	Vacuum pressure	
	Seals	<b>Glued</b>
	Weight	<b>5 KG</b>
<b>Frame or neck</b>	Stainless steel 2B sheet in 1,4301 or 1,4307 (AISI 304/304L) or 1,4404 (AISI 316L) 80, 90, 100 mm height thickness of 2, 3 or 4 mm, inside access with +/- 2 mm tolerance. Finishes: picklrd or shot blasted with non smooth inside welding.	
<b>Cover</b>	2B Stainless steel sheets 1,4301 or 1,4307 (AISI 304/304L) or 1,4404 (AISI 316L) in 1,5, 2, 3 mm. Electro polished.	
<b>Components</b>	Stainless steel 1,4301 or 1,4307 (AISI 304/304L) Chromed brass hand wheel or stainless steel hand nut 1,4404 with or without bronze insert.	

